

Printed from www.chemquest.com.au

IDENTIFICATION			
8.1 Product Name:	CRAFTSMART FABRIC GLUE		
8.2 Other Names:	EVA Adhesive		
8.3 Manufacturer's Product Code:	1110		
UN Number:	none allocated		
Dangerous Goods Class:	not applicable		
Packaging Group:	not applicable		
Subsidiary Risk:	not applicable		
8.6 Hazchem Code:	not applicable		
8.8 Poisons Schedule No.:	Not scheduled		
8.10 Use:	To adhere all types of materials together, such as craftwood, paper, plastic, glass etc.		
Linked barcodes:	Barcode		Description
Other:			
Physical Description		Other Properties	
8.16 Appearance:	Thin white liquid with a slight solvent odour.	8.23a Shock Sensitivity:	EVA Adhesive
8.17 Boiling Point/Melting Point:	boiling: Initial boiling point 100 degrees celsius. Melting point: not applicable	8.23b Corrosiveness:	
8.18 Vapour Pressure:	not available	8.23c Oxidising Properties:	
8.19 Specific Gravity:	1.02	8.23d Reactivity with Common Substances:	
8.20 Flash Point:	not applicable	8.23e Auto-Ignition Temperature:	not applicable
8.21 Flammability Limits:	Non Flammable.	8.23f Evaporation Rate:	
8.23 Solubility in Water:	Completely dispersable	8.23g Vapour Density:	
Other:		8.23h Odour Threshold:	
		8.23i pH:	Approx 7.0

		8.23j Solubility in Organic Solvents:	
		8.23k Per Cent Volatiles:	
		8.23l Volatile Organic Compounds:	water
		8.23m Bulk Density:	
		Other:	molecular weight : not applicable
Ingredients	8.27 Chemical Name	8.28 CAS No.	8.29 Proportion
	Synthetic Polymer Emulsion		60-100%
	Water	7732-18-5	10-30%
	Plasticiser		0-20%
	Toluene	108-88-3	0-5%
9 HEALTH HAZARD INFORMATION		10 PRECAUTIONS FOR USE	
9.2 Health Effects		10.4 Exposure Standards:	This product contains toluene. The product (wet)odour may cause discomfort under the influence of elevated temperatures or in confined area. The use of a solvent vapour mask under these circumstances may be advisable.Toluene:OSHA PEL:TWA 200p.p.m.;CL 300; PK 500/10M ACGIH TLV : TWA 100p.p.m. ;STEL 150p.p.m.
Acute		10.10 Engineering Controls:	Use with adequate ventilation.
Swallowed:	Ingestion may result in nausea and vomiting.	10.13 Personal Protection:	Wearing of the following personal protective equipment may be advisable. Chemically resistant gloves. Avoid skin and eye contact. Avoid inhaling the vapour when working in a confined area. use in a well ventilated area only.
Eye:	Mild eye irritant. May cause watering of eyes. May cause soreness.	10.18 Flammability:	Non flammable . Product residue, following evaporation of liquid content will burn in the prescence of an ignition source.
Skin:	Repeated or prolonged contact with skin may result in irritation and dermatitic effects.	Other:	
Inhaled:	Practically non harmful by inhalation. May cause irritation to the nose and throat. Not normally an inhalation risk due	11 SAFE HANDLING INFORMATION	

	to low vapour pressure at ambient temperature.		
Chronic		11.1 Storage and Transport:	Store in a cool,dry place. Store in original containers. Transport in original containers. Do not freeze avoid storing on concrete during cold conditions.
9.30 First Aid		11.4 Spills and Disposal:	In the event of large spills isolate leaking containers and stop leak if safe to do so. Prevent contamination of drains and waterways. Clean up using a shovel. Collect and seal in properly labelled drums for disposal. Normally suitable for disposal at approved land waste site. Wash away residues with water, In the event of a small spill;Scrape up mop up and wash to drain with copious volumes of water.Wipe up residue with a cloth. Dispose of contaminated rags in a waste bin.
Swallowed:	Thoroughly rinse mouth with water. Give plenty of water to drink. Do Not induce vomiting. Seek medical advice.	11.11 Fire/Explosion Hazard:	Only the dried residue will burn emitting acrid smoke and irritating fumes. If the dried residue has ignited, decomposition products may include:Carbon dioxide (CO ₂) and carbon monoxide (CO) Extinguish the fire using (CO ₂) dry chemical or foam. Fire fighters to use self contained breathing apparatus if risk of exposure to product of decomposition.
Eye:	Irrigate with copious quantities of water for fifteen (15) minutes. Eyelid to be held open. Seek medical assistance if effect persists.	Other:	Conditions to avoid: Extreme heat (greater tha 100deg cel) Incompatible Materials: Strong oxidisers. Hazardous Polymerisation: Will not occur.
Skin:	Wash contaminated skin with plenty of soap and water. Remove contaminated clothing and wash before re-use. If irritation occurs seek medical advice.		
Inhaled:	Remove victim from exposure - avoid becoming a casualty. Recovery should be rapid after removal from exposure. Seek		

	medical advice if effects persist.		
First Aid Facilities			
9.33 Advice to Doctor	Treat symptomatically		
Other			
GENERAL			
General	CRAFTSMART FABRIC GLUE		
SUPPLIER			
Supplier	CSA Trading Pty Ltd trading as Craftsmart ABN 86 124 105 004		
Supplier Date	May 2013		
13 CONTACT POINT:			
13.1 Contact Title:			
13.1 Contact 'Phone:	Poison Info Centre (Australia 13 1126: New Zealand 0800 764 766		
13.1 Contact Pager:			

MSDS Supplied by: CSA Trading Pty Ltd trading as Craftsmart ABN 86 124 105 004 on date: May 2013